

Fill in the form below, complete sections 1 through 7 and email to: veris-sales@armstronginternational.com

Requested By: _____

Date: _____ Tag#: _____ E-mail: _____


Phone: _____ Fax: _____

Company: _____ Address: _____ City, State, Zip: _____

End User:

Company Name: _____ City: _____ State, Zip: _____

1. Enter Pipe Dimensions



Pipe Size _____ Sch _____

Pipe ID _____ Wall _____ Pipe Mat'l _____

Wall

2. Pipe Orientation (Check one box)



(H) Horizontal



(V) Vertical

3. Enter Flow Conditions

Fluid Name:		Maximum	Normal	Minimum	Units
Flow Rate					
All Fluids	Pressure @ Flow				
	Temperature @ Flow				
Gas	Specific Gravity, or				
	Molecular Weight				
Liquid	Specific Gravity				
Steam	VeraCalc Program can calculate Density from Temperature and Pressure				

Special Instructions


4. Select Model Accelabar 316SS (Check one box in each category)

AFS Flanged (ANSI):

- 150# 300#
 600# ABS Bevel for Weld
 ATS MNPT Threaded Ends (2" meter only)

Specify Accelabar Meter Size:

- 1" (DN25) 6" (DN150)
 2" (DN50) 8" (DN200)
 3" (DN75) 10" (DN250)
 4" (DN100) 12" (DN300)



5. Select Instrument Head (Check one box)

Instrument Head Connections (Select Remote or Direct Mount Transmitter — Sold Separately)				
Direct Mount Transmitter (Flanged 450°F/232°C Max.)		Remote Mount Transmitter (1/2" NPT)		
Manifold	Transmount	Valve	Regular	Parallel
Integral		Integral		
<input type="checkbox"/> M	<input type="checkbox"/> F	<input type="checkbox"/> T	<input type="checkbox"/> R	<input type="checkbox"/> P

6. Select Instrument Valves or Manifold, RTD & Cable (Optional)

Manifolds (Optional)				Instrument Valves (Optional)	
Direct Mount				Remote Mount	
3-Valve		5-Valve		Needle	Gate
Soft Seat	Hard Seat	Soft Seat	Hard Seat	1/2" NPT	1/2" NPT
<input type="checkbox"/> F3SC (CS) <input type="checkbox"/> F3SS (SS)	<input type="checkbox"/> F3HC (CS) <input type="checkbox"/> F3HS (SS)	<input type="checkbox"/> F5SC (CS) <input type="checkbox"/> F5SS (SS)	<input type="checkbox"/> F5HC (CS) <input type="checkbox"/> F5HS (SS)	<input type="checkbox"/> C2NC (CS) <input type="checkbox"/> C2NS (SS)	<input type="checkbox"/> C2GC (CS) <input type="checkbox"/> C2GS (SS)

Code	RTD in Thermowell
<input type="checkbox"/> H1	Standard Temperature, 500°F (260°C) Max., Explosion Resistant
<input type="checkbox"/> HT	High Temperature, 900°F (482°C) Max., Moisture and Dust Resistant
Code	Connection Cable to Transmitter (Direct Mount Only)
<input type="checkbox"/> XP	Explosion Resistant
<input type="checkbox"/> N4	Moisture and Dust Resistant

7. Transmitter

Supplied By

Veris Others

